





Surface coated, white, natural and easy to disperse calcium powder. This product is the result of high purity and white limestone/Calcite powder.

SPECIFICATION CHART:

Particle Size Distribution	
Mean Particle Size(d50) µm Max	2.00
Top Cut (d98) µm Max	10.00
Specific Surface Area (cm³/gm)	20000
Residue on 45 µm sieve (%)	Nil
Optical Properties	
Whiteness % (ASTM E313)	96±1
Yellowness Index (ASTM 313)	1.1
Brightness (ISO 247)	94±1
Calcium Carbonate % (CaCO₃)	97±1
Acid Insoluble %	1.50 Max
Loss on Ignition (LOI)	43±1
Hardness (Moh's Scale)	3.00
Other Properties	
Bulk Density, loose (gm/100ml)	0.66
Bulk Density, packed (gm/100ml)	1-1.25
Moisture (%), Max	< 0.3
Specific Gravity	2.7
pH in 10% Aqueous Suspension	9
Coating % Stearic Acid	1-1.2






Applications -











Printing Ink







Cable Compounding



Paints

Note: The above values are based on measurements carried out according to our quality management systems.

CONTACT US -

Registered Office: Neco Chambers, Off No. 404/405, Plot No. 48, Sector-11, CBD Belapur, Navi Mumbai - 400614.

Corporate Office: Lime chemicals ltd, 21/22 Regency chambers, N.L.Road, NEAR Nandi Cinema, Bandra West, Mumbai - 400050

Mobile: +91-99876 83652

Tel: 62360356

Email: esales@limechem.com

Website: www.limechem.com

